

MATERIAL SAFETY DATA SHEET

Section 1

IDENTIFICATION OF THE MATERIAL AND SUPPLIER

COMPANY	Delshine Chemicals
ABN NUMBER	21 009 447 769
ADDRESS	Unit 1 / 30 Prindiville Drive, Wangara
FACSIMILE NUMBER	(08) 9309 4334
TELEPHONE NUMBER	(08) 9309 4222
EMERGENCY TELEPHONE	041 992 7281 (After hours)
EMAIL	delshine-chemicals@bigpond.com
WEB SITE	www.delshinechemicals.com

BRAND NAME – Non Fumic Acid
TRADE NAME – Sulphuric Acid 34 %
SHIPPING NAME (section 14)

USE – PH Alteration in Swimming Pools

RESTRICTIONS – Store away from combustible materials and metal.

Section 2

HAZARDS CLASSIFICATION / IDENTIFICATION

CLASSIFIED AS : **HAZARDOUS** – According to the criteria of NOHSC and classified as a dangerous good according to the ADG code.

UN NUMBER : 2796

Emergency Overview : Causes severe burns. May be fatal if swallowed. Strong inorganic mist containing sulfuric acid can cause cancer. Inhalation may cause damage to respiratory tract lungs.

Swallowed : Can kill if swallowed. Will cause severe damage to the mucous membranes. May cause severe burns to mouth , throat and stomach. Ingestion can cause nausea , vomiting and abdominal pain.

Eyes : Corrosive to eyes ; contact can cause corneal burns. Permanent eye damage, including loss of sight , may occur.

Skin : Highly corrosive to skin. Causes severe burns.

Inhaled : Harmful by inhalation. Possible harmful corrosive effects. High concentrations of vapour can cause severe irritation of the respiratory tract.

CONTINUE HAZARDS CLASSIFICATION / IDENTIFICATION

- RISK PHRASES :** R35 – Causes severe burns.
R41 – Risk of serious eye damage
- SAFETY PHRASES:** S1 / 2 – Keep locked up and out of reach of children.
S26 - In case of contact with eyes rinse immediately with plenty of water and seek medical advice.
S30 - Never add water to the product.
S36/37/39 Wear suitable protective clothing, gloves @ eye/face protection
S45 - In case of accident or you feel unwell seek medical advice immediately (show label whenever possible)

Section 3 COMPOSITION / INFORMATION OF INGREDIENTS

Chemical Entity:	CAS No:	Proportion (% mass)
Sulfuric Acid	7664-93-9	34
Water	7732-18-15	66

Section 4 FIRST AID MEASURES

GET MEDICAL ASSISTANCE FOR ALL CASES OF OVER EXPOSURE.

Eyes : Immediately flush thoroughly with water for at least 15 minutes.

Inhalation : Remove to fresh air ; give artificial respiration if breathing has stopped.

Ingestion : Do not induce vomiting ; get immediate medical attention. If conscious give water , milk , or milk of magnesia.

Remove contaminated clothing and wash before reuse.

First Aid Facilities: **Ensure an eye bath and safety shower are available and ready for use.**

Section 5 FIRE FIGHTING MEASURES

Flash point (°C) Noncombustible

Flammable Limits LEL (%) : Not available ; (%) : Not available

Extinguishing Media : Use any suitable media for adjacent material.

Fire Fighting Procedures : Wear self contained breathing apparatus and protective clothing.

Fire and Explosion Hazards : Thermal decomposition produces toxic fumes.

HAZCHEM CODE : 2R

Section 6

ACCIDENTAL RELEASE MEASURES

Spill Response : Evacuate the area of all unnecessary personnel. Wear suitable protective equipment listed under Exposure / Personal Protection. Eliminate any ignition sources until the area is determined to be free from explosion or fire hazards. Contain the release and eliminate its sources , if this can be done with out risk. Take up and containerize for proper disposal as described under Disposal. Comply with Federal , State and local regulations on reporting releases. Use soda ash to neutralize small spills.

Section 7

HANDLING AND STORAGE

Storage: Store in high density polyethylene or glass fibre-reinforced plastic tanks that Conforms to AS2634-1983 or other approved standards. Keep container closed. Store in a cool area away from combustible materials or metal powders.

Handling : Do not breathe vapour or mist. Do not get in eyes , on skin or on clothing.

Class : 8

Section 8

EXPOSURE CONTROLS / PERSONAL PROTECTION

NOHSC Exposure - Sulfuric Acid : TWA 1 mg/m³ , STEL 3 mg/m³

Odour Threshold : > 1mg/m³ IDLH Value: 80mg/m³

Respiratory Protection : Combination particulate / gas respirator , Class B , (Inorganic vapour). If workplace exposure limits of product or any component is exceeded, an AS1715/1716 approved air supplied respirator is advised.

Engineering and / or administrative controls should be implemented to reduce exposure. Material must be handled or transferred in an approved fume hood or with equivalent ventilation. Protective gloves must be worn to prevent skin contact. (Neoprene or equivalent) Safety glasses with side shields must be worn at all times. Impervious protective clothing should be worn to prevent skin contact.

Work / Hygiene Practices : Wash thoroughly after handling. Do not take internally. Eye wash and safety equipment should be readily available.

Prolonged exposure to mist vapours can cause erosion of teeth , chronic irritation of eyes, nose and throat and chronic inflammation of airways. 77-98% acid causes 2nd and 3rd degree burns of skin on short contact and is very injurious to the eyes.

Section 12 **ECOLOGICAL INFORMATION**

Environmental Fate : When released into the soil, this material may leach into groundwater. When released into the air this material may be removed from the atmosphere to a moderate extent by wet deposition. When released into the air this material may be removed from the atmosphere to a moderate extent by dry deposition. Environmental Toxicity : LD50 Flounder 100 to 330mg/1/48 hr aerated water /conditions of bioassay not specified; Shrimp 80 to 90 mg/1/48hr aerated water conditions of bioassay not specified ; LC50 Prawn 42.54 ppm/48hr aerated salt water conditions of bioassay not specified. Bluegill in fresh water : 24.5 ppmk/24hr conditions of bioassay not specified. This material may be toxic to aquatic life.

Section 13 **DISPOSAL CONSIDERATIONS**

Specified Technology - Neutralize to pH 6-9. Contact your local permitted waste disposal site for permissible treatment sites.

Section 14 **TRANSPORT INFORMATION**

UN NUMBER : 2796

UN PROPER SHIPPING NAME : Sulfuric Acid (< 51%)

CLASS: 8 **PACKING GROUP**: 11 **HAZCHEM CODE**: 2R

SUBSIDIARY RISK

SUSDP SCHEDULE 6

Section 15 **REGULATORY INFORMATION**

SUSDP Labelling : Schedule 6 Poison. **First Aid** : For advice contact Poisons Information Centre (Phone Australia 131 126) or a doctor at once. If swallowed DO NOT induce vomiting. If in eyes hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the Poisons Information Centre or a doctor or for at least 15 minutes. If skin or hair contact occurs remove contaminated clothing and flush skin and hair with running water .

Safety Directions Corrosive Avoid contact with eyes and skin.

NOHSC Labelling- C Corrosive R35 Causes severe burns, S1/2 Keep locked up and out of reach of children, S26 In case of contact with eyes rinse immediately with plenty of water and seek medical advice, S30 Never add water to this product , S45 In case of accident or you feel unwell seek medical advice immediately (show label whenever possible)

Section 16	OTHER INFORMATION
-------------------	--------------------------

NFPA Hazard Ratings : Health : 2 ; Flammability : 0 ; Reactivity : 0

DATE OF LAST REVISION OF MATERIAL SAFETY DATA SHEET :

15th October 2010

CONTACT POINT – Les Buss – TELEPHONE (08) 9309 4222

AUTHORISATION FOR ISSUE _____ **DATE** ____/____/____

Les Buss

The above information is accurate to the best of the knowledge available to us. However since data safety and government regulations are subject to change and the conditions of handling and use, or misuse are beyond our control we make no warranty, whether express or implied, with respect to completeness or continuing accuracy of the information contained herein and disclaims all liability for reliance thereon. Users should satisfy themselves that they have all current data relevant to their particular use.

END OF M.S.D.S